






Réf : CA001

6 TORONS DE 7 FILS (6+1)











Désignation	Diamètre		Rupture		Poids kg/ml
	mm	Tol. %	kg	kN	
 02	2	-1 +7	239	2,35	0,013
 03	3	-1 +7	539	5,29	0,035
 04	4	-1 +8	958	9,40	0,050
 05	5	-1 +8	1 497	14,69	0,087
 06	6	-1 +7	2 157	21,16	0,132

Câblage croisé droite préformé - **Acier galvanisé non graissé** - Âme textile - Classe de résistance 1 770 N/mm² - Norme ISO 2408 - *Usage général*

Réf : CA002

7 TORONS DE 7 FILS (6+1)











Désignation	Diamètre		Rupture		Poids kg/ml
	mm	Tol. %	kg	kN	
 1,5	1,5	-1 +7	146	-	-
 02	2	-1 +7	258	2,54	0,015
 2,5	2,5	-1 +7	420	-	-
 03	3	-1 +7	583	5,72	0,034
 04	4	-1 +6	1 036	10,17	0,061
 05	5	-1 +6	1 619	15,89	0,095
 06	6	-1 +5	2 332	22,88	0,137

Câblage croisé droite préformé - **Acier galvanisé non graissé** - Âme métallique - Classe de résistance 1 770 N/mm² - Norme ISO 2408 - *Usage général*

Réf : CA003

6 TORONS DE 19 FILS (12+6+1)



Désignation	Diamètre		Rupture		Poids kg/ml
	mm	Tol. %	kg	kN	
 03	3	-	500	4,90	0,031
 04	4	-	890	8,70	0,055
 05	5	-	1 390	13,60	0,086
 06	6	-	2 000	19,60	0,125
 07	7	-	2 850	27,90	0,170
 08	8	-1 +4	3 812	37,40	0,221
 09	9	-1 +4	4 821	47,30	0,280
 10	10	-1 +4	5 953	58,40	0,346
11	11	-1 +4	7 206	70,70	0,419
12	12	-1 +4	8 572	84,10	0,498
13	13	-1 +4	10 061	98,70	0,585
14	14	-1 +4	11 671	114,50	0,678
16	16	-1 +4	15 239	149,50	0,886
18	18	-1 +4	19 286	189,20	1,120
20	20	-1 +4	23 812	233,60	1,380

Câblage croisé droite préformé - **Acier galvanisé non graissé** - Âme textile - Classe de résistance 1 770 N/mm² - Norme ISO 2408 (à partir du Ø 8 et au-delà) - *Usage général (plus souple que CA0001)*